HDW043_001L

4.3 Inch, 480xRGBx800, 16.7M Colors, IPS screen, Capacitive touch



own rechno.



• Display

ltem	Parameter	Description	
Color	16.7M (16777216) colors	24 bit color 8R8G8B	
Panel Type	IPS	IPS process TFT LCM ,wide viewing angle	
Viewing Angle	85/85/85/85 (L/R/U/D)	Best View: symmetrical	
Active Area (A.A.)	93.6mm (W) * 56.2mm (H)	480*800	
View Area (V.A.)	94.0mm (W) * 56.6mm (H)	480*800	
Resolution	480x800	-	
Backlight	LED	>20000 hours (Time of the brightness decaying to 50% on the condition of continuous working with the maximum brightness)	
Brightness	250nit	-	
Note:You can use dynamic screen saver wallpapers to avoid afterimages caused by fixed page display for a long time.			

• Voltage & Current

ltem	Conditions	Min	Тур	Мах	Unit
Power Voltage	-	3.6 5.0		6.0	V
Operation Current	VCC = +5V, Backlight on	-	· C-0	-	mA
	VCC = +5V, Backlight off	-		-	mA
Recommended power supply: 5V 1A DC					

Reliability Test

ltem	Conditions	Min	Тур	Мах	Unit
Working Temperature	60%RH at 5V voltage	-10	25	60	°C
Storage Temperature	- 203	-20	25	70	°C
Working Humidity	25 ℃	10%	60%	90%	RH
Protective Paint	CI-	-	None	-	-

• Interface

ltem	Description
Socket	HDMI interface
USB Interface	Yes
SD Card Slot	None

• Peripheral

Peripheral	
Peripheral	Capacitive touch panel

Professional, Creditable, Successful

Packing Capacity & Dimension


Dimension				
Dimension	103.7(W)* 63.0(H)*15.20(T)mm			
Net Weight	90g			
Packing Capacity				
Model	Size	Layer	Quantity/Layer	Quantity(Pcs)
Carton1:	220mm(L)*160mm(W)*47mm (H)	1	2	2
Carton2:	250mm(L)*200mm(W)*80mm (H)	2	2	4
Carton3:	320mm(L)*270mm(W)*80mm (H)	2	4	8
Carton4:	450mm(L)*350mm(W)*300mm(H)	2	30	60
Carton5:	600mm(L)*450mm(W)*300mm(H)	2	60	120

Disclaimer:

DWIA

1, The product design is subject to alternation and improvement without prior notice.

. e the stable s e sales personnel 2, There are multiple parallel raw materials coexisting to guarantee the stable supply. If customers have particular raw material preferences or requirements, please contact the sales personnel.



DWIN

Inarmer, for you Professional, Creditable, Successful

Record of Revision

Ver	Revise Date	Content	Editor
00	2022-12-15	First Edition	Kaya
01	2024-05-13	Update Temperature Range	YML

Please contact us if you have any questions about the use of this document or our products, or if you would like to know the latest information about our products:

Customer service Tel: +86-400-018-9008

Customer service E-mail: dwinhmi@dwin.com.cn

Website: www.dwin-global.com

DWIN Developer Forum: https://forums.dwin-global.com/index.php/forums

Thank you all for continuous support of DWIN, and your approval is the driving force of our progress!

Important Disclaimer

DWIN reserves the right to make any changes to product designs without prior notice.

Customers should ensure strictly adhering to all the relevant standards and requirements during the product application process, including but not limited to functional safety, information security, and regulatory provisions. DWIN shall not bear any joint and several liability for any consequences that may arise from customers' adoption of DWIN products. In particular, for risks that may lead to significant property losses, environmental hazards, personal injury, or even death, especially in high-risk application areas such as military applications, flammable and explosive places, and life-saving medical equipment, customers should independently assess the risks and take corresponding preventive and protective measures. DWIN shall not bear any relevant responsibility.