

unisystem

UST070SSRNCU00

7.0" IPS LCD-TFT MODULE SPECIFICATION

Key Specifications

Parameter	Specification
LCD Type	IPS TFT / Transmissive / Normally Black
Size (Diagonal)	7.0"
Viewing Direction	Full Viewing (All)
Outside Dimensions (W x H x D)	180.00 x 119.00 x 7.81 mm
Active Area (W x H)	154.21 x 85.92 mm
Pixel Pitch (W x H)	0.1506 x 0.1432 mm
Resolution	1024 x 600 (RGB)
Brightness	900 cd / m ² (typ.)
Contrast Ratio	1000:1 (typ.)
Color Depth	16.7 M
Pixel Arrangement	RGB Stripe
Interface	RGB (24-bit parallel)
LCD Driver	JD9165BA
With / Without Touch	With Capacitive Touch (CTP)
CTP Driver	ILI2520 (USB / I2C)
Surface Treatment	Glare
Operating / Storage Temp.	-20°C ~ +70°C / -30°C ~ +80°C
Weight	223 g

Revision Table

Rev.	Date	Description
1.0	2026-10-13	First issue

Contents


1. Coding System	4
2. Mechanical Drawing	5
3. Absolute Maximum Ratings	6
4. DC Characteristics	6
5. Backlight Characteristics	6
6. Touch Screen Panel Specifications	7
7. Optical Characteristics	7
7.1 Definition of Response Time	8
7.2 Definition of Contrast Ratio	9
7.3 Definition of Viewing Angles	9
7.4 Definition of Color Appearance	10
7.5 Definition of Surface Luminance, Uniformity and Transmittance	11
8. Block Diagram and Power Supply	12
9. Interface Pins Definition	12
10. Timing Characteristics	15
10.1 RGB Input Timing Table	15
10.2 RGB Input Timing Diagram	16
10.3 RGB AC Characteristics	17
11. Quality Assurance	18
11.1 Purpose	18
11.2 Standard for Quality Test	18
11.3 Agreement Items	18
11.4 Standard of the Product Visual Inspection	18
11.5 Inspection Specification for the TFT module	19
11.6 Classification of Defects	25
11.7 Identification / Marking Criteria	25
11.8 Packing	25
12. Reliability Specification	26
13. Precautions	27
13.1 Safety	27
13.2 Handling	27
13.3 Storage	27
13.4 Operation	27
13.5 Static Electricity	27
14. Legal Information	28
15. Contact Information	29

1. Coding System

1	2	3	4	5	6	7	8	9	10
US	T	070	S	S	R	N	C	U	00

No.	Parameter	Options
1	Manufacturer	Unisystem
2	Display Type	T – TFT
3	Display Size	070 – 7", 101 – 10.1", 121 – 12.1", 156 – 15.6"
4	Model Series	S – “Core” Standard Brightness IPS, H – “Pro” High Brightness IPS, L – “Lite” IPS
5	Resolution	M – 800x480, S – 1024x600 (WSVGA), W – 1280x800 (WXGA), X – 1024x768 (XGA), F – 1920x1080 (FHD)
6	Interface	L – LVDS, M – MIPI DSI, R – RGB, D – eDP, H – HDMI and USB-C
7	Frame	F – With Mounting Metal Frame, N – Without Mounting Metal Frame
8	Touch Panel	N – Without Touch Panel, C – With Projected Capacitive Touch Panel
9	Cover Glass Specification	N – Without Cover Glass, E – Rectangular Glass with Optical Bonding, U – Rounded Glass with Optical Bonding
10	Version	00 – base series, 10 – improved series

2. Mechanical Drawing



3. Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit
Supply Voltage	V_{DD}	-0.3	3.96	V
Storage temperature	T_{STG}	-30	+80	°C
Operating temperature	T_{OP}	-20	+70	°C

Note 1: If T_a is below 50°C, the maximum humidity is 90%RH; if T_a is over 50°C, the absolute humidity shall not exceed that of 60%RH at 50°C.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C or below, and the background will become darker during high-temperature operation.

4. DC Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage	V_{DD}	2.8	3.3	3.6	V
Logic High level input voltage	V_{IH}	$0.8 \cdot V_{DD}$	-	V_{DD}	V
Logic Low level input voltage	V_{IL}	GND	-	$0.2 \cdot V_{DD}$	V
Logic High level Output voltage	V_{OH}	$0.9 \cdot V_{DD}$	-	V_{DD}	V
Logic Low level Output voltage	V_{OL}	GND	-	$0.1 \cdot V_{DD}$	V
Current Consumption (All White)	I_{DD}	-	132	-	mA

5. Backlight Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$T_a = 25^\circ\text{C}$, $I_F = 25\text{mA}$ / LED	8.1	9.3	9.9	V
Forward Current	I_F	$T_a = 25^\circ\text{C}$, $I_F = 25\text{mA}$ / LED	-	250	-	mA
Power Dissipation	P_D	-	-	2325	-	mW
Uniformity	-	Avg	-	80	-	%
LED working life (25°C)	-	-	-	100,000	-	Hrs
Drive method	Constant current					
LED Configuration	30 White LEDs (3 LEDs in string and 10 groups in parallel)					

Note 1: LED lifetime is defined as the time until the brightness drops to 50% of its initial value. The test is conducted under ambient air flow, at $T_a = 25 \pm 2^\circ\text{C}$, 60%RH $\pm 5\%$, $I_F = 25\text{mA}$ / LED.

6. Touch Screen Panel Specifications

Item	CTP Description	
1	IC	ILI2520
2	Interface	USB / I2C
3	Operating voltage	5V / 3.3V
4	Interface signal voltage	3.3V / 3.3V
5	Surface hardness	≥ 6H
6	Operating temperature	-20°C ~ +70°C
7	Storage temperature	-30°C ~ +80°C
8	Strengthened Type	Chemical
9	Transmittance	≥ 85%
10	Origin of coordinates	Top Left
11	Resolution	1024 x 600


7. Optical Characteristics

Ta = 25°C, Power = 3.3V

Backlight On (Transmissive Mode)	Item		Symbol	Condition	Specification			Unit
					Min.	Typ.	Max.	
	Luminance with CTP (I _F = 25mA / LED)		L _V		-	900	-	cd / m ²
	Contrast ratio (See 7.2)		CR		700	1000	-	
	Response time (See 7.1)		T _R + T _F		-	30	35	ms
	Chromaticity Transmissive (See 7.4)	Red	X _R		0.550	0.600	0.650	
			Y _R		0.325	0.375	0.425	
		Green	X _G		0.283	0.333	0.383	
			Y _G		0.517	0.567	0.617	
		Blue	X _B		0.079	0.129	0.179	
			Y _B		0.035	0.085	0.135	
		White	X _W		0.260	0.310	0.360	
			Y _W		0.300	0.350	0.400	
	Viewing Angle (See 7.3)	Horizontal	θ _{X+}	Center CR ≥ 10	70	80	-	Deg.
			θ _{X-}		70	80	-	
		Vertical	φ _{Y+}		70	80	-	
φ _{Y-}			70		80	-		
NTSC Ratio (Gamut)				45	50	-	%	

7.1 Definition of Response Time

7.1.1 Normally Black Type (Negative)




Tr is the time it takes to change from non-selected state with relative luminance 10% to selected state with relative luminance 90%.

Tf is the time it takes to change from selected state with relative luminance 90% to non-selected state with relative luminance 10%.

Note: Measuring machine: LCD-5100

7.1.2 Normally White Type (Positive)



Tr is the time it takes to change from non-selected state with relative luminance 90% to selected state with relative luminance 10%.

Tf is the time it takes to change from selected state with relative luminance 10% to non-selected state with relative luminance 90%.

Note: Measuring machine: LCD-5100 or equivalent

7.2 Definition of Contrast Ratio

Contrast is measured perpendicularly to the display surface in transmissive mode.


The measurement condition is:

Measuring Equipment	Eldim or equivalent
Measuring Point Diameter	3mm / 1mm
Measuring Point Location	Active Area center point
Test pattern	A: All pixels white
	B: All pixels black
Contrast setting	Maximum

Definition: CR (Contrast) = Luminance of White Pixel / Luminance of Black Pixel

7.3 Definition of Viewing Angles

Measuring machine: LCD-5100 or equivalent




7.4 Definition of Color Appearance

R, G, B and W are defined by (x, y) coordinates on the CIE chromaticity diagram.

NTSC = area of RGB triangle / area of NTSC triangle x 100%

Measuring picture: Red, Green, Blue and White (Measuring machine: BM-7)



7.5 Definition of Surface Luminance, Uniformity and Transmittance

Using the transmissive mode measurement approach, measure the white screen luminance of the display panel and backlight.


Surface Luminance: $L_V = \text{average } (L_{P1}:L_{P9})$

Uniformity = $\text{Minimum } (L_{P1}:L_{P9}) / \text{Maximum } (L_{P1}:L_{P9}) \times 100\%$


Transmittance = $L_V \text{ on LCD} / L_V \text{ on Backlight} \times 100\%$

Note: Measuring machine: BM-7

Note: Test 3 brightness points below 3.5 inches (point 2 / 5 / 8), test 5 brightness points between 3.5–7 inches (point 1 / 3 / 5 / 7 / 9), and test 9 brightness points above 7 inches (point 1 to 9).



8. Block Diagram and Power Supply



9. Interface Pins Definition

LCM PIN:

No.	Symbol	Function
1-2	LED+	LED Anode
3-4	LED-	LED Cathode
5	GND	Ground
6	NC	Not connect
7	V _{DD}	Power supply
8	MODE	DE / SYNC mode selects H: DE mode. L: SYNC mode
9	DE	Data enable signal, active high to enable data
10	VSYNC	Vertical synchronizing signal

No.	Symbol	Function
11	HSYNC	Horizontal synchronizing signal
12-19	B7-B0	Blue data signal
20-27	G7-G0	Green data signal
28-35	R7-R0	Red data signal
36	GND	Ground
37	DCLK	Clock for input data
38	GND	Ground
39	L / R	Horizontal inversion ¹⁾
40	U / D	Vertical inversion ²⁾
41-43	NC	Not connect
44	RSTB	Global reset pin
45-46	NC	Not connect
47	STBYB	Standby mode selection ³⁾
48	GND	Ground
49-50	NC	Not connect

Note

1) Horizontal inversion (Default pull Low)

L / R	Function
1	Right → Left
0	Left → Right

2) Vertical inversion (Default pull Low)

U / D	Function
1	Bottom → Top
0	Top → Bottom

3) Standby mode selection (Default pull High)

If not used, please fix this pin at V_{DD} level.

STBYB	Function
H	Normal mode
L	Standby mode

CTP PIN:

No.	Symbol	Function
1	USB_GND	Ground
2	USB_VDD	Power Supply
3	USB_D-	Data-
4	USB_D+	Data+
5	I2C_GND	CTP Ground
6	I2C_VDD	CTP Power Supply
7	I2C_RST	CTP Reset input signal, active low
8	I2C_SCL	CTP Clock input signal
9	I2C_INT	CTP Interrupt output signal
10	I2C_SDA	CTP Data input / output signal

CN1 PIN:

No.	Symbol	Function
1	USB_VDD	Power Supply
2	USB_D-	Data-
3	USB_D+	Data+
4	USB_GND	Ground

CN2 PIN:

No.	Symbol	Function
1	I2C_GND	CTP Ground
2	I2C_VDD	CTP Power Supply
3	I2C_RST	CTP Reset input signal, active low
4	I2C_SCL	CTP Clock input signal
5	I2C_INT	CTP Interrupt output signal
6	I2C_SDA	CTP Data input / output signal


10. Timing Characteristics

10.1 RGB Input Timing Table


24-bit parallel RGB Input Timing	Symbol	1024RGBx600			Unit
		Min.	Typ.	Max.	
DCLK Frequency	-	41.4	51.2	67.2	MHZ
Horizontal Total	t_{ht}	1114	1344	1400	DCLK
Hsync Pulse width	t_{hs}	1	24	HBP-1	DCLK
Horizontal Back Porch	t_{hb}	60	160	160	DCLK
Horizontal Valid Data	t_{hd}	1024			DCLK
Horizontal Front Porch	t_{hfp}	30	160	216	DCLK
Vertical Total	t_{vt}	620	635	800	THT
Vsync Pulse Width	t_{vs}	1	2	VBP-1	THT
Vertical Back Porch	t_{vb}	8	23	100	THT
Vertical Valid Data	t_{vd}	600			THT
Vertical Front Porch	t_{vfp}	12	12	100	THT

10.2 RGB Input Timing Diagram

● Horizontal timing



● Vertical timing




24-bit parallel RGB mode horizontal/vertical input timing

10.3 RGB AC Characteristics

Input data / sync parameters

Parameter	Symbol	Spec.			Unit
		Min.	Typ.	Max.	
CLKIN period	T_{cph}	14	-	-	ns
CLKIN duty ratio	T_{cw}	40	50	60	%
Data setup time	T_{dsu}	5	-	-	ns
Data hold time	T_{dhd}	5	-	-	ns
VSD setup time	T_{ss}	5	-	-	ns
VSD hold time	T_{sh}	5	-	-	ns
HSD setup time	T_{ss}	5	-	-	ns
HSD hold time	T_{sh}	5	-	-	ns
DEN setup time	T_{ss}	5	-	-	ns
DEN hold time	T_{sh}	5	-	-	ns



Input signal timing

11. Quality Assurance

11.1 Purpose

This Quality Assurance standard ensures the quality of LCD module products supplied to the customer.

11.2 Standard for Quality Test

11.2.1 Sampling Plan:

GB/T2828.1-2012

Single sampling, general inspection level II

11.2.2 Sampling Criteria:

Visual inspection: AQL 1.5

Electrical functional: AQL 0.65.

11.2.3 Reliability Test:

For detailed requirements refer to Section 12 Reliability Specification.

11.3 Agreement Items

The following situations shall be negotiated with the customer:

11.3.1 Any discrepancy in the standard of quality assurance.

11.3.2 Additional requirements to be added to the product specification.

11.3.3 Any other special problem.


11.4 Standard of the Product Visual Inspection

11.4.1 Appearance inspection:

11.4.1.1 The inspection must be carried out under an illumination of about 1000 – 1500 lx, and the viewing distance must be 30 cm ± 2 cm.

11.4.1.2 The viewing angle should be 45° from the vertical line without reflected light, or follow the customer's viewing angle specifications.

11.4.1.3 Definition of area: A Zone: Active Area, B Zone: Viewing Area.






11.4.2 Basic principle:





11.4.2.1 A set of samples to indicate the limit of acceptable quality level must be discussed by both us and the customer when a dispute occurs.




11.4.2.2 New items must be added when necessary.

11.5 Inspection Specification for the TFT module

No.	Item	Criteria (Unit: mm)									
01	Black / White spot Foreign material (Round type) Pinholes Stain Particles inside cell. (Minor defect)		<table><tr><th>Size \ Area</th><th>Acc. Qty</th></tr><tr><td>$\phi \leq 0.20$</td><td>Ignore</td></tr><tr><td>$0.20 < \phi \leq 0.50$</td><td>$N \leq 3$</td></tr><tr><td>$0.50 < \phi$</td><td>0</td></tr></table>	Size \ Area	Acc. Qty	$\phi \leq 0.20$	Ignore	$0.20 < \phi \leq 0.50$	$N \leq 3$	$0.50 < \phi$	0
			Size \ Area	Acc. Qty							
			$\phi \leq 0.20$	Ignore							
			$0.20 < \phi \leq 0.50$	$N \leq 3$							
$0.50 < \phi$	0										
$\phi = (a + b) / 2$											
The distance between 2 defects should be more than 5 mm.											

No.	Item	Criteria (Unit: mm)			
02	Electrical Defect (Major defect)	Bright dot	Display Area	Total	Note 1
			$N \leq 2$	$N \leq 2$	
		Dark dot	$N \leq 4$	$N \leq 4$	
		Total dot	$N \leq 4$	$N \leq 4$	
		Mura	Not visible through 5% ND filters.		Note 2
Remark: 1. A bright dot caused by a scratch or a foreign object is judged according to item 01.					
03	Black and White line Scratch Foreign material (Line type) (Minor defect)				
					
		Length	Width	Acc. Qty	
		/	$W \leq 0.1$	Ignore	
		$L \leq 2.5$	$0.1 < W \leq 0.2$	3	
$L > 2.5$	$0.2 < W$	0			
Total			3		
The distance between 2 defects should be more than 3 mm. Scratches not viewable through the back of the display are acceptable.					
04	Glass Crack (Major defect)				
		Cracks of any type are not allowed, as a crack may enlarge.			


No.	Item	Criteria (Unit: mm)										
05	Glass Chipping Pad Area: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c > 3.0, b < 1.0$</td><td>1</td></tr><tr><td>$c < 3.0, b < 1.0$</td><td>3</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c > 3.0, b < 1.0$	1	$c < 3.0, b < 1.0$	3	$a < \text{Glass Thickness}$			
Length and Width	Acc. Qty											
$c > 3.0, b < 1.0$	1											
$c < 3.0, b < 1.0$	3											
$a < \text{Glass Thickness}$												
06	Glass Chipping Rear of Pad Area: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c > 3.0, b < 1.0$</td><td>1</td></tr><tr><td>$c < 3.0, b < 1.0$</td><td>2</td></tr><tr><td>$c < 3.0, b < 0.5$</td><td>4</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c > 3.0, b < 1.0$	1	$c < 3.0, b < 1.0$	2	$c < 3.0, b < 0.5$	4	$a < \text{Glass Thickness}$	
Length and Width	Acc. Qty											
$c > 3.0, b < 1.0$	1											
$c < 3.0, b < 1.0$	2											
$c < 3.0, b < 0.5$	4											
$a < \text{Glass Thickness}$												
07	Glass Chipping Except Pad Area: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c > 3.0, b < 1.0$</td><td>1</td></tr><tr><td>$c < 3.0, b < 1.0$</td><td>2</td></tr><tr><td>$c < 3.0, b < 0.5$</td><td>4</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c > 3.0, b < 1.0$	1	$c < 3.0, b < 1.0$	2	$c < 3.0, b < 0.5$	4	$a < \text{Glass Thickness}$	
Length and Width	Acc. Qty											
$c > 3.0, b < 1.0$	1											
$c < 3.0, b < 1.0$	2											
$c < 3.0, b < 0.5$	4											
$a < \text{Glass Thickness}$												
08	Glass Corner Chipping: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c < 3.0, b < 3.0$</td><td>Ignore</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c < 3.0, b < 3.0$	Ignore	$a < \text{Glass Thickness}$					
Length and Width	Acc. Qty											
$c < 3.0, b < 3.0$	Ignore											
$a < \text{Glass Thickness}$												





No.	Item	Criteria (Unit: mm)								
09	Glass Burr: (Minor defect)	 <table><thead><tr><th>Length</th><th>Acc. Qty</th></tr></thead><tbody><tr><td>$F < 1.0$</td><td>Ignore</td></tr></tbody></table> Glass burr must not affect assembly and module dimensions.	Length	Acc. Qty	$F < 1.0$	Ignore				
Length	Acc. Qty									
$F < 1.0$	Ignore									
10	FPC Defect: (Minor defect)	 10.1 Dent, pinhole width $a < w / 3$. (w: circuitry width.) 10.2 Open circuit is unacceptable. 10.3 No oxidation, contamination and distortion.								
11	Bubble on Polarizer (Minor defect)	<table><thead><tr><th>Diameter</th><th>Acc. Qty</th></tr></thead><tbody><tr><td>$\phi \leq 0.30$</td><td>Ignore</td></tr><tr><td>$0.30 < \phi \leq 0.50$</td><td>$N \leq 2$</td></tr><tr><td>$0.50 < \phi$</td><td>$N = 0$</td></tr></tbody></table>  $b < 1 / 2a$ Note: In high-temperature and high-humidity experiments, bubbles do not disperse.	Diameter	Acc. Qty	$\phi \leq 0.30$	Ignore	$0.30 < \phi \leq 0.50$	$N \leq 2$	$0.50 < \phi$	$N = 0$
Diameter	Acc. Qty									
$\phi \leq 0.30$	Ignore									
$0.30 < \phi \leq 0.50$	$N \leq 2$									
$0.50 < \phi$	$N = 0$									



No.	Item	Criteria (Unit: mm)	
12	Dent on Polarizer (Minor defect)	Diameter	Acc. Qty
		$\phi \leq 0.25$	Ignore
		$0.25 < \phi \leq 0.50$	$N \leq 4$
		$0.50 < \phi$	None
13	Bezel	13.1 No rust or distortion on the bezel. 13.2 No visible fingerprints, stains or other contamination.	
14	PCB	14.1 No distortion or contamination on PCB terminals. 14.2 All components on the PCB must be the same as documented on the BOM / component layout. 14.3 Follow IPC-A-600F.	
15	Soldering	Follow the IPC-A-610C standard.	
16	Electrical Defect (Major defect)	The following defects must be rejected: 16.1 Missing vertical / horizontal line. 16.2 Abnormal Display. 16.3 No function or no display. 16.4 Current exceeds product specifications. 16.5 LCD viewing angle defect. 16.6 No Backlight. 16.7 Dark Backlight. 16.8 Touch panel not functioning.	

Remark: A broken LCD panel shall be rejected. Defects outside the LCD viewing area are acceptable.

Inspection Specification for the Capacitive Touch Panel

No.	Item	Criteria (Unit: mm)
01	Chipping Pad Area (cover lens not included): (Major defect)	 Chipping of any type is not allowed, as it seriously affects the product's function.

No.	Item	Criteria (Unit: mm)																						
02	Chipping Except Pad Area (cover lens not included): (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c < 1.5, b < 1$</td><td>$N \leq 5$</td></tr><tr><td colspan="2">$a < 1 / 2$ Glass Thickness</td></tr></table>	Length and Width	Acc. Qty	$c < 1.5, b < 1$	$N \leq 5$	$a < 1 / 2$ Glass Thickness																	
Length and Width	Acc. Qty																							
$c < 1.5, b < 1$	$N \leq 5$																							
$a < 1 / 2$ Glass Thickness																								
03	Corner Chipping (cover lens not included): (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c < 1.5, b < 0.5$</td><td>Ignore</td></tr><tr><td colspan="2">$a < 1 / 2$ Glass Thickness</td></tr></table>	Length and Width	Acc. Qty	$c < 1.5, b < 0.5$	Ignore	$a < 1 / 2$ Glass Thickness																	
Length and Width	Acc. Qty																							
$c < 1.5, b < 0.5$	Ignore																							
$a < 1 / 2$ Glass Thickness																								
04	Crack: (Minor defect)	 Cracks of any type are not allowed, as a crack may enlarge.																						
05	Cover lens must be without any chips, cracks or other damage when viewed from the front.																							
06	Same / Different color spot	 <table><tr><th colspan="2">D: diameter, W: width, L: length</th></tr><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td>$D < 0.20$</td><td>Ignore</td></tr></table> Active Area: <table><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td>$0.20 < D \leq 0.30$</td><td>2</td></tr><tr><td>$0.30 < D \leq 0.50$</td><td>1</td></tr><tr><td>$D > 0.5$</td><td>NG</td></tr></table> Viewing Area: <table><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td>$D < 0.20$</td><td>Ignore</td></tr><tr><td>$0.20 < D \leq 0.5$</td><td>3</td></tr><tr><td>$D > 0.5$</td><td>NG</td></tr></table> The distance between 2 defects should be more than 15 mm.	D: diameter, W: width, L: length		Diameter	Acc. Qty	$D < 0.20$	Ignore	Diameter	Acc. Qty	$0.20 < D \leq 0.30$	2	$0.30 < D \leq 0.50$	1	$D > 0.5$	NG	Diameter	Acc. Qty	$D < 0.20$	Ignore	$0.20 < D \leq 0.5$	3	$D > 0.5$	NG
D: diameter, W: width, L: length																								
Diameter	Acc. Qty																							
$D < 0.20$	Ignore																							
Diameter	Acc. Qty																							
$0.20 < D \leq 0.30$	2																							
$0.30 < D \leq 0.50$	1																							
$D > 0.5$	NG																							
Diameter	Acc. Qty																							
$D < 0.20$	Ignore																							
$0.20 < D \leq 0.5$	3																							
$D > 0.5$	NG																							

No.	Item	Criteria (Unit: mm)		
07	Cover lens line scratch 			
		Length	Width	Acc. Qty
		/	$W \leq 0.08$	Ignore
		$L \leq 5$	$0.08 < W \leq 0.15$	2
		$L \leq 3$	$0.15 < W \leq 0.20$	1
		-	$W > 0.2$	NG
		$L > 5$	-	NG
The distance between 2 defects should be more than 15 mm.				
08	Printing sawtooth 			
		Length	Width	Acc. Qty
		/	$W \leq 0.2$	2
		$L \leq 2$	$0.2 < W \leq 0.3$	1
		$L \leq 2$	$W > 0.3$	NG

11.6 Classification of Defects

11.6.1 Visual defects (except missing / wrong label) are treated as minor defects, and electrical defects as major defects.

11.6.2 Two minor defects are equal to one major defect in lot sampling inspection.

11.7 Identification / Marking Criteria

Any unit with illegible, wrong, double or missing marking / label shall be rejected.


11.8 Packing

11.8.1 There should be no damage to the outer carton box; each packaging box should have one identical label.

11.8.2 Modules inside the package box should have a compliance mark.

11.8.3 All direct package materials shall offer ESD protection.

Note 1: Bright dot is defined as a dot whose defective area is larger than 50% of one sub-pixel area.



Bright dot: a dot-size bright defect on a black display pattern. It can be recognized through a 2% transmittance filter at an eye-to-panel distance of 350 mm $\pm$ 50 mm.

Dark dot: a cyan, magenta or yellow dot-size defect on a white display pattern. It can be recognized through a 5% transmittance filter at an eye-to-panel distance of 350 mm $\pm$ 50 mm.

Note 2: Mura — areas of the display that appear darker / brighter than the surrounding background.

12. Reliability Specification

No.	Item	Condition	Quantity	Criteria
1	High Temperature Operating	70°C, 96Hrs	2	GB/T2423.2-2008
2	Low Temperature Operating	-20°C, 96Hrs	2	GB/T2423.1-2008
3	High Humidity Storage	60°C, 90%RH, 96Hrs	2	GB/T2423.3-2016
4	High Temperature Storage	80°C, 96Hrs	2	GB/T2423.2-2008
5	Low Temperature Storage	-30°C, 96Hrs	2	GB/T2423.1-2008
6	Thermal Cycling Test Storage	-20°C $\leftrightarrow$ 70°C 30 min 5 min 30 min after 5 cycle, Restore 2H at 25°C Power off	2	GB/T2423.22-2012
7	Packing vibration	Frequency range: 10Hz ~ 50Hz Acceleration of gravity: 5G X, Y, Z: 30 min for each direction.	-	GB/T5170.14-2009
8	Electrostatic Discharge	Air: $\pm$ 4kV, 150pF / 330 Ω Contact: $\pm$ 2kV, 150pF / 330 Ω	2	GB/T17626.2-2018
9	Drop Test (Packaged)	Height: 72cm (weight $\leq$ 10kg), 60cm (weight > 10kg), 1 corner, 3 edges, 6 surfaces.	-	GB/T2423.7-2018

Note 1: No cosmetic defects and no loss of operational function are allowed.

Note 2: The total current consumption should be below twice the initial value.

13. Precautions

13.1 Safety

13.1.1 The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.

13.1.2 Since the liquid crystal cells are made of glass, do not subject them to strong impacts. Handle with care.

13.2 Handling

13.2.1 Store and use within ratings in order to keep performance and prevent damage.

13.2.2 Do not wipe the cover glass with a dry cloth, as it might cause scratches. If the surface of the cover glass needs to be cleaned, wipe it swiftly with cotton or another soft cloth soaked with IPA or petroleum benzine; do not use other chemicals.

13.3 Storage

13.3.1 Do not store the LCD module beyond the specified temperature ranges.

13.3.2 Strong light exposure causes degradation of the polarizer and color filter.

13.4 Operation

13.4.1 Response time will increase at lower temperatures.

13.4.2 The display may change color at different temperatures.

13.4.3 Mechanical disturbance during operation, such as pressing on the display area, may cause temporary display non-uniformity.

13.4.4 Do not connect or disconnect the LCM to or from the system when power is on.

13.4.5 Never use the LCM under abnormal conditions of high temperature and high humidity.

13.4.6 The module has high-frequency circuits. Sufficient suppression of electromagnetic interference shall be provided by the system manufacturer. Grounding and shielding methods may be important to minimize the interference.

13.4.7 Do not display a fixed pattern for a long time (we recommend no longer than one hour), as it may cause image sticking due to the TFT structure.

13.5 Static Electricity

13.5.1 This unit contains CMOS LSIs, so care must be taken to avoid electrostatic charge, e.g. by grounding the human body.

13.5.2 The normal static prevention measures should be observed for work clothes and benches.

13.5.3 The module should be kept in anti-static bags or other containers resistant to static for storage.

14. Legal Information

CE Marking

CE marking is obligatory only for complete end products. Unisystem display modules are semifinished goods designed to be integrated into finished devices and, therefore, are not CE marked.

Warranty

Unisystem grants a warranty for the proper operation of the goods for a period of 24 months from the date of delivery. If, as a result of a warranty claim, the customer receives a defect-free item as a replacement, the warranty period shall start anew from the moment the replacement is received.

Right to Change Specifications

Unisystem reserves the right to make changes to the product specifications, dimensions, and materials without prior notice in order to improve reliability, function, or design. It is the buyer's responsibility to verify that the datasheet is current before placing an order.

Intellectual Property

This document and the technical information herein are the exclusive property of Unisystem and may be subject to pending or granted patents. Reproduction or disclosure of this document without prior written permission is strictly prohibited. No intellectual property licenses are implicitly conveyed.

Limitation of Liability

Images and graphics used in this document are for illustrative purposes only. Unisystem shall not be liable to the buyer or any third party for any indirect, incidental, special, or consequential damages (including, without limitation, lost profits or business opportunities) arising from the use of its products or services.

High-Risk Applications Disclaimer

Unisystem products are not designed, intended, or authorized for use in safety-critical or high-risk applications where failure could directly result in personal injury, death, or severe environmental damage (e.g., life support machines, aerospace navigation, nuclear facilities). Using Unisystem products in such high-risk activities is entirely at the buyer's risk, and the buyer agrees to fully indemnify and hold Unisystem harmless from any damages or claims resulting from such unauthorized use.

15. Contact Information

unisystem

UNISYSTEM SP. Z O.O.

Nowy Świat 36
80-299 Gdańsk
Poland

+48 58 761 54 20
office@unisystem.com

EU VAT No.:
PL5842741076