



UST070HSLNCE00

7.0" IPS LCD-TFT MODULE SPECIFICATION

Key Specifications

Parameter	Specification
LCD Type	IPS TFT / Transmissive / Normally Black
Size (Diagonal)	7.0"
Viewing Direction	Full Viewing (All)
Outside Dimensions (W x H x D)	165.10 x 100.10 x 11.94 mm
Active Area (W x H)	154.21 x 85.92 mm
Pixel Pitch (W x H)	0.1506 x 0.1432 mm
Resolution	1024 x 600 (RGB)
Brightness	1900 cd / m ² (typ.)
Contrast Ratio	1000:1 (typ.)
Color Depth	16.7 M
Pixel Arrangement	RGB Stripe
Interface	LVDS
LCD Driver	JD9165BA
With / Without Touch	With Capacitive Touch (CTP)
CTP Driver	ILI2520 (USB / I2C)
Surface Treatment	Glare
Operating / Storage Temp.	-20°C ~ +70°C / -30°C ~ +80°C
Weight	334 g

Revision Table

Rev.	Date	Description
1.0	2026-10-06	First issue
1.1	2026-10-07	Minor updates

Contents


1. Coding System	4
2. Mechanical Drawing	5
3. Absolute Maximum Ratings	6
4. DC Characteristics	6
5. Backlight Characteristic	6
6. Touch Screen Panel Specifications	7
7. Optical Characteristics	7
7.1 Definition of Response Time	8
7.2 Definition of Contrast Ratio	9
7.3 Definition of Viewing Angles	9
7.4 Definition of Color Appearance	10
7.5 Definition of Surface Luminance, Uniformity and Transmittance	11
8. Block Diagram and Power Supply	12
9. Interface Pins Definition	12
10. AC characteristics	15
10.1 LVDS data input format	15
10.2 LVDS timing characteristic	16
11. Quality Assurance	17
11.1 Purpose	17
11.2 Standard for Quality Test	18
11.3 Nonconforming Analysis & Disposition	18
11.4 Agreement Items	18
11.5 Standard of the Product Visual Inspection	18
11.6 Inspection Specification for the TFT module	19
11.7 Classification of Defects	25
11.8 Identification / marking criteria	25
11.9 Packing	25
12. Reliability Specification	27
13. Precautions and Warranty	27
13.1 Safety	27
13.2 Handling	27
13.3 Storage	28
13.4 Operation	28
13.5 Static Electricity	28
14. Legal information	29
15. Contact Information	30

1. Coding System

1	2	3	4	5	6	7	8	9	10
US	T	070	H	S	L	N	C	E	00

No.	Parameter	Options
1	Manufacturer	Unisystem
2	Display Type	T – TFT
3	Display Size	070 – 7", 101 – 10.1", 121 – 12.1", 156 – 15.6"
4	Model Series	S – “Core” Standard Brightness IPS, H – “Pro” High Brightness IPS, L – “Lite” IPS
5	Resolution	M – 800x480, S – 1024x600 (WSVGA), W – 1280x800 (WXGA), X – 1024x768 (XGA), F – 1920x1080 (FHD)
6	Interface	L – LVDS, M – MIPI DSI, R – RGB, D – eDP, H – HDMI and USB-C
7	Frame	F – With Mounting Metal Frame, N – Without Mounting Metal Frame
8	Touch Panel	N – Without Touch Panel, C – With Projected Capacitive Touch Panel
9	Cover Glass Specification	N – Without Cover Glass, E – Rectangular Glass with Optical Bonding, U – Rounded Glass with Optical Bonding
10	Version	00 – base series, 10 – improved series

office@unisystem.com
www.unisystem.com



3. Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit
Supply Voltage	V_{DD}	-0.3	3.96	V
Storage temperature	T_{STG}	-30	+80	°C
Operating temperature	T_{OP}	-20	+70	°C

Note 1: If T_a is below 50°C, the maximum humidity is 90%RH, if T_a is over 50°C, absolute humidity shall not exceed that of 60%RH at 50°C.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C or below, and the background will become darker during high-temperature operation.

4. DC Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage	V_{DD}	2.8	3.3	3.6	V
Logic High level input voltage	V_{IH}	$0.8 \cdot V_{DD}$	-	V_{DD}	V
Logic Low level input voltage	V_{IL}	GND	-	$0.2 \cdot V_{DD}$	V
Logic High level Output voltage	V_{OH}	$0.9 \cdot V_{DD}$	-	V_{DD}	V
Logic Low level Output voltage	V_{OL}	GND	-	$0.1 \cdot V_{DD}$	V
Current Consumption (All White)	I_{DD}	-	125	-	mA

5. Backlight Characteristic

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$T_a = 25^\circ\text{C}$, $I_F = 80\text{mA}$ / LED	21.6	24	26.4	V
Forward Current	I_F	$T_a = 25^\circ\text{C}$, $I_F = 80\text{mA}$ / LED	-	240	-	mA
Power dissipation	P_D	-	-	5760	-	mW
Uniformity	-	Avg	-	80	-	%
LED working life (25 °C)	-	-	-	100,000	-	Hrs
Drive method	Constant current					
LED Configuration	24 White LEDs (8 LEDs in string and 3 groups in parallel)					

Note 1: LED lifetime is defined as follows: The final brightness is at 50% of original brightness. The test is conducted under ambient air flow, at $T_a = 25 \pm 2^\circ\text{C}$, 60%RH $\pm$ 5%, $I_F = 80\text{mA}$ / LED.

6. Touch Screen Panel Specifications

Item	CTP Description	
1	IC	ILI2520
2	Interface	USB / I2C
3	Operation voltage	5V / 3.3V
4	Interface signal voltage	3.3V / 3.3V
5	Surface hardness	≥ 6H
6	Operation temperature	-20°C ~ +70°C
7	Storage temperature	-30°C ~ +80°C
8	Strengthened Type	Chemical
9	Transmittance	≥ 85%
10	Origin of coordinates	Top Left
11	Resolution Ratio	1024 x 600


7. Optical Characteristics

Ta = 25°C, Power = 3.3V

Backlight On (Transmissive Mode)	Item		Symbol	Condition	Specification			Unit
					Min.	Typ.	Max.	
	Luminance with CTP (I _F = 80mA / LED)		L _V		-	1900	-	cd / m ²
	Contrast ratio (See 7.2)		CR		700	1000	-	
	Response time (See 7.1)		T _R + T _F		-	30	35	ms
	Chromaticity Transmissive (See 7.4)	Red	X _R		0.576	0.626	0.676	
			Y _R		0.290	0.340	0.390	
		Green	X _G		0.272	0.322	0.372	
			Y _G		0.522	0.572	0.622	
		Blue	X _B		0.098	0.148	0.198	
Y _B				0.034	0.084	0.134		
White		X _W		0.241	0.291	0.341		
		Y _W		0.293	0.343	0.393		
Viewing Angle (See 7.3)	Horizontal	θ _{X+}	Center CR ≥ 10	70	80	-	Deg.	
		θ _{X-}		70	80	-		
	Vertical	φ _{Y+}		70	80	-		
		φ _{Y-}		70	80	-		
NTSC Ratio (Gamut)				45	50	-	%	

7.1 Definition of Response Time

7.1.1 Normally Black Type (Negative)




Tr is the time it takes to change from non-selected state with relative luminance 10% to selected state with relative luminance 90%.

Tf is the time it takes to change from selected state with relative luminance 90% to non-selected state with relative luminance 10%.

Note: Measuring machine: LCD-5100

7.1.2 Normally White Type (Positive)



Tr is the time it takes to change from non-selected state with relative luminance 90% to selected state with relative luminance 10%.

Tf is the time it takes to change from selected state with relative luminance 10% to non-selected state with relative luminance 90%.

Note: Measuring machine: LCD-5100 or equivalent

7.2 Definition of Contrast Ratio

Contrast is measured perpendicularly to the display surface in transmissive mode.


The measurement condition is:

Measuring Equipment	Eldim or Equivalent
Measuring Point Diameter	3mm / 1mm
Measuring Point Location	Active Area center point
Test pattern	A: All Pixels white
	B: All Pixel black
Contrast setting	Maximum

Definitions: CR (Contrast) = Luminance of White Pixel / Luminance of Black Pixel

7.3 Definition of Viewing Angles

Measuring machine: LCD-5100 or equivalent




7.4 Definition of Color Appearance

R,G,B and W are defined by (x, y) on the CIE chromaticity diagram

NTSC = area of RGB triangle / area of NTSC triangle x 100%

Measuring picture: Red, Green, Blue and White (Measuring machine: BM-7)



7.5 Definition of Surface Luminance, Uniformity and Transmittance

Using the transmissive mode measurement approach, measure the white screen luminance of the display panel and backlight.


Surface Luminance: $L_V = \text{average } (L_{P1}:L_{P9})$

Uniformity = $\text{Minimal } (L_{P1}:L_{P9}) / \text{Maximal } (L_{P1}:L_{P9}) \times 100\%$


Transmittance = $L_V \text{ on LCD} / L_V \text{ on Backlight} \times 100\%$

Note: Measuring machine: BM-7

Note: Test 3 brightness points below 3.5 inches (point 2 / 5 / 8), test 5 brightness points between 3.5–7 inches (point 1 / 3 / 5 / 7 / 9), and test 9 brightness points above 7 inches (point 1 to 9).



8. Block Diagram and Power Supply



9. Interface Pins Definition

LCM PIN:

No.	Symbol	Function
1	NC	No Connection
2-3	V _{DD} (3.3V)	Power supply
4	NC	No Connection
5	RESET	Global reset pin, active low. (Default pull High)
6	STBYB	Standby mode selection ¹⁾
7	GND	Ground
8	RXIN0-	Negative LVDS Differential data input
9	RXIN0+	Positive LVDS Differential data input

No.	Symbol	Function
10	GND	Ground
11	RXIN1-	Negative LVDS Differential data input
12	RXIN1+	Positive LVDS Differential data input
13	GND	Ground
14	RXIN2-	Negative LVDS Differential data input
15	RXIN2+	Positive LVDS Differential data input
16	GND	Ground
17	RXCLKIN-	Negative LVDS Differential clock input
18	RXCLKIN+	Positive LVDS Differential clock input
19	GND	Ground
20	RXIN3-	Negative LVDS Differential data input
21	RXIN3+	Positive LVDS Differential data input
22	GND	Ground
23-24	NC	No Connection
25	GND	Ground
26-27	NC	No Connection
28	SELB	Used as 6-bit / 8-bit input select.
29	VESA / JEIDA	8-bit input format select for LVDS mode ²⁾
30	GND	Ground
31-32	LED-	Backlight Cathode.
33	L / R	Horizontal inversion ³⁾
34	U / D	Vertical inversion ⁴⁾
35-38	NC	No Connection
39-40	LED+	Backlight Anode.

Note

1) Standby mode selection (Default pull High)

If not used, please fix this pin at V_{DD} level.

STBYB	Function
H	Normal mode
L	Standby mode

2) 8-bit input format select for LVDS mode (Default pull High)

VESA / JEIDA	Function
1	VESA format
0	JEIDA format

3) Horizontal inversion (Default pull Low)

SHLR	Function
1	Right → Left
0	Left → Right

4) Vertical inversion (Default pull Low)

UPDN	Function
1	Bottom → Top
0	Top → Bottom

CTP PIN:

No.	Symbol	Function
1	USB_GND	Ground
2	USB_VDD	Power Supply
3	USB_D-	Data-
4	USB_D+	Data+
5	I2C_GND	CTP Ground
6	I2C_VDD	CTP Power Supply
7	I2C_RST	CTP Reset input signal, active low
8	I2C_SCL	CTP Clock input signal
9	I2C_INT	CTP Interrupt output signal
10	I2C_SDA	CTP Data input / output signal

CN1 PIN:


No.	Symbol	Function
1	USB_VDD	Power Supply
2	USB_D-	Data-
3	USB_D+	Data+
4	USB_GND	Ground

CN2 PIN:


No.	Symbol	Function
1	I2C_GND	CTP Ground
2	I2C_VDD	CTP Power Supply
3	I2C_RST	CTP Reset input signal, active low
4	I2C_SCL	CTP Clock input signal
5	I2C_INT	CTP Interrupt output signal
6	I2C_SDA	CTP Data input / output signal

10. AC characteristics


10.1 LVDS data input format



6-bit RGB LVDS input timing



8-bit RGB LVDS VESA input timing



8-bit RGB LVDS JEIDA input timing

10.2 LVDS timing characteristic

LVDS Input Timing	Symbol	1024RGB x 600		
		Min	Typ	Max
DCLK Frequency	-	41.4	51.2	67.2
Horizontal Total	t_{ht}	1114	1344	1400
Hsync Pulse width	t_{hs}	1	24	HBP-1
Horizontal Back Porch	t_{hb}	60	160	160
Horizontal Valid Data	t_{hd}	1024		
Horizontal Front Porch	t_{hfp}	30	160	216
Vertical Total	t_{vt}	620	635	800
Vsync Pulse Width	t_{vs}	1	2	VBP-1
Vertical Back Porch	t_{vb}	8	23	100
Vertical Valid Data	t_{vd}	600		
Vertical Front Porch	t_{vfp}	12	12	100

Parameter	Symbol	Spec.			Unit	Condition
		Min.	Typ.	Max.		
Clock frequency	R_{xFCLK}	20	-	71	MHz	Refer to input timing table for each display resolution
Input data skew margin	T_{RSKM}	-0.2	-	0.2	UI	$ VID = 200mV$ $RxVCM = 1.2V$ $1UI = 1 / (R_{xFCLK} \times 7)$
Clock high time	T_{LVCH}	-	$4 / (7 \times R_{xFCLK})$	-	ns	
Clock low time	T_{LVCL}	-	$3 / (7 \times R_{xFCLK})$	-	ns	
PLL wake-up time	T_{enPLL}	-	-	150	us	

LVDS figure

This Quality Assurance standard ensures the quality of LCD module products supplied to customer.

11.2 Standard for Quality Test

11.2.1 Sampling Plan:

GB/T2828.1-2012

Single sampling, general inspection level II

11.2.2 Sampling Criteria:

Visual inspection: AQL 1.5

Electrical functional: AQL 0.65.

11.2.3 Reliability Test:

For detailed requirements refer to Section 12 Reliability Specification.

11.3 Nonconforming Analysis & Disposition

11.3.1 Nonconforming analysis:

11.3.1.1 The customer should provide complete information on the non-conforming sample for their complaints.

11.3.1.2 After receipt of detailed information from customer, the analysis of nonconforming parts usually should be finished in one week.

11.3.1.3 If the analysis cannot be finished on time, the customer will be notified with the progress status.

11.3.2 Disposition of nonconforming:

11.3.2.1 Non-conforming product over PPM level will be replaced.

11.3.2.2 The cause of non-conformance will be analyzed. Corrective action will be discussed and implemented.

11.4 Agreement Items

The following situations shall be negotiated with the customer:

11.4.1 Any discrepancy in the standard of quality assurance.

11.4.2 Additional requirement to be added in product specification.

11.4.3 Any other special problem.


11.5 Standard of the Product Visual Inspection

11.5.1 Appearance inspection:

11.5.1.1 The inspection must be under illumination about 1000 – 1500 lx, and the viewing distance must be 30 cm ± 2 cm.

11.5.1.2 The viewing angle should be 45° from the vertical line without reflected light, or follow the customer's viewing angle specifications.

11.5.1.3 Definition of area: A Zone: Active Area, B Zone: Viewing Area,







11.5.2 Basic principle:





11.5.2.1 A set of samples to indicate the limit of acceptable quality level must be discussed by both us and customer when a dispute occurs.




11.5.2.2 New items must be added when necessary.

11.6 Inspection Specification for the TFT module

No.	Item	Criteria (Unit: mm)									
01	Black / White spot Foreign material (Round type) Pinholes Stain Particles inside cell. (Minor defect)		<table><tr><th>Size \ Area</th><th>Acc. Qty</th></tr><tr><td>$\phi \leq 0.20$</td><td>Ignore</td></tr><tr><td>$0.20 < \phi \leq 0.50$</td><td>$N \leq 3$</td></tr><tr><td>$0.50 < \phi$</td><td>0</td></tr></table>	Size \ Area	Acc. Qty	$\phi \leq 0.20$	Ignore	$0.20 < \phi \leq 0.50$	$N \leq 3$	$0.50 < \phi$	0
			Size \ Area	Acc. Qty							
$\phi \leq 0.20$	Ignore										
$0.20 < \phi \leq 0.50$	$N \leq 3$										
$0.50 < \phi$	0										
			$\phi = (a + b) / 2$ Distance between 2 defects should be more than 5 mm.								

No.	Item	Criteria (Unit: mm)																		
02	Electrical Defect (Major defect)	Bright dot	Display Area	Total	Note1															
			$N \leq 2$	$N \leq 2$																
		Dark dot	$N \leq 4$	$N \leq 4$																
		Total dot	$N \leq 4$	$N \leq 4$																
		Mura	Not visible through 5% ND filters.		Note 2															
Remark: 1. Bright dot caused by scratch and foreign object is judged according to item 1.																				
03	Black and White line Scratch Foreign material (Line type) (Minor defect)																			
																				
		<table><thead><tr><th>Length</th><th>Width</th><th>Acc. Qty</th></tr></thead><tbody><tr><td>/</td><td>$W \leq 0.1$</td><td>Ignore</td></tr><tr><td>$L \leq 2.5$</td><td>$0.1 < W \leq 0.2$</td><td>3</td></tr><tr><td>$L > 2.5$</td><td>$0.2 < W$</td><td>0</td></tr><tr><td colspan="2">Total</td><td>3</td></tr></tbody></table>				Length	Width	Acc. Qty	/	$W \leq 0.1$	Ignore	$L \leq 2.5$	$0.1 < W \leq 0.2$	3	$L > 2.5$	$0.2 < W$	0	Total		3
		Length	Width	Acc. Qty																
		/	$W \leq 0.1$	Ignore																
$L \leq 2.5$	$0.1 < W \leq 0.2$	3																		
$L > 2.5$	$0.2 < W$	0																		
Total		3																		
Distance between 2 defects should be more than 3 mm. Scratches not viewable through the back of the display are acceptable.																				
04	Glass Crack (Major defect)																			
		A crack may enlarge, any type is not allowed.																		


No.	Item	Criteria (Unit: mm)										
05	Glass Chipping Pad Area: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c > 3.0, b < 1.0$</td><td>1</td></tr><tr><td>$c < 3.0, b < 1.0$</td><td>3</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c > 3.0, b < 1.0$	1	$c < 3.0, b < 1.0$	3	$a < \text{Glass Thickness}$			
Length and Width	Acc. Qty											
$c > 3.0, b < 1.0$	1											
$c < 3.0, b < 1.0$	3											
$a < \text{Glass Thickness}$												
06	Glass Chipping Rear of Pad Area: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c > 3.0, b < 1.0$</td><td>1</td></tr><tr><td>$c < 3.0, b < 1.0$</td><td>2</td></tr><tr><td>$c < 3.0, b < 0.5$</td><td>4</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c > 3.0, b < 1.0$	1	$c < 3.0, b < 1.0$	2	$c < 3.0, b < 0.5$	4	$a < \text{Glass Thickness}$	
Length and Width	Acc. Qty											
$c > 3.0, b < 1.0$	1											
$c < 3.0, b < 1.0$	2											
$c < 3.0, b < 0.5$	4											
$a < \text{Glass Thickness}$												
07	Glass Chipping Except Pad Area: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c > 3.0, b < 1.0$</td><td>1</td></tr><tr><td>$c < 3.0, b < 1.0$</td><td>2</td></tr><tr><td>$c < 3.0, b < 0.5$</td><td>4</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c > 3.0, b < 1.0$	1	$c < 3.0, b < 1.0$	2	$c < 3.0, b < 0.5$	4	$a < \text{Glass Thickness}$	
Length and Width	Acc. Qty											
$c > 3.0, b < 1.0$	1											
$c < 3.0, b < 1.0$	2											
$c < 3.0, b < 0.5$	4											
$a < \text{Glass Thickness}$												
08	Glass Corner Chipping: (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>$c < 3.0, b < 3.0$</td><td>Ignore</td></tr><tr><td colspan="2">$a < \text{Glass Thickness}$</td></tr></table>	Length and Width	Acc. Qty	$c < 3.0, b < 3.0$	Ignore	$a < \text{Glass Thickness}$					
Length and Width	Acc. Qty											
$c < 3.0, b < 3.0$	Ignore											
$a < \text{Glass Thickness}$												




No.	Item	Criteria (Unit: mm)								
09	Glass Burr: (Minor defect)	 <table><thead><tr><th>Length</th><th>Acc. Qty</th></tr></thead><tbody><tr><td>$F < 1.0$</td><td>Ignore</td></tr></tbody></table> Glass burr must not affect assembly and module dimensions.	Length	Acc. Qty	$F < 1.0$	Ignore				
Length	Acc. Qty									
$F < 1.0$	Ignore									
10	FPC Defect: (Minor defect)	 10.1 Dent, pinhole width $a < w / 3$. (w: circuitry width.) 10.2 Open circuit is unacceptable. 10.3 No oxidation, contamination and distortion.								
11	Bubble on Polarizer (Minor defect)	<table><thead><tr><th>Diameter</th><th>Acc. Qty</th></tr></thead><tbody><tr><td>$\phi \leq 0.30$</td><td>Ignore</td></tr><tr><td>$0.30 < \phi \leq 0.50$</td><td>$N \leq 2$</td></tr><tr><td>$0.50 < \phi$</td><td>$N = 0$</td></tr></tbody></table>  $b < 1 / 2a$ Note: In high-temperature and high-humidity experiments, bubbles do not disperse.	Diameter	Acc. Qty	$\phi \leq 0.30$	Ignore	$0.30 < \phi \leq 0.50$	$N \leq 2$	$0.50 < \phi$	$N = 0$
Diameter	Acc. Qty									
$\phi \leq 0.30$	Ignore									
$0.30 < \phi \leq 0.50$	$N \leq 2$									
$0.50 < \phi$	$N = 0$									



No.	Item	Criteria (Unit: mm)	
12	Dent on Polarizer (Minor defect)	Diameter	Acc. Qty
		$\phi \leq 0.25$	Ignore
		$0.25 < \phi \leq 0.50$	$N \leq 4$
		$0.50 < \phi$	None
13	Bezel	13.1 No rust, distortion on the Bezel. 13.2 No visible fingerprints, stains or other contamination.	
14	PCB	14.1 No distortion or contamination on PCB terminals. 14.2 All components on the PCB must be the same as documented on the BOM / component layout. 14.3 Follow IPC-A-600F.	
15	Soldering	Follow IPC-A-610C standard	
16	Electrical Defect (Major defect)	The below defects must be rejected. 16.1 Missing vertical / horizontal segment, 16.2 Abnormal Display. 16.3 No function or no display. 16.4 Current exceeds product specifications. 16.5 LCD viewing angle defect. 16.6 No Backlight. 16.7 Dark Backlight. 16.8 Touch Panel no function.	

Remark: LCD Panel Broken shall be rejected. Defect out of LCD viewing area is acceptable.

Inspection Specification for the Capacitive Touch Panel

No.	Item	Criteria (Unit: mm)
01	Chipping Pad Area (cover lens not included): (Major defect)	 Chipping seriously affects the product's function, any type is not allowed.

No.	Item	Criteria (Unit: mm)																						
02	Chipping Except Pad Area (cover lens not included): (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>c < 1.5, b < 1</td><td>N ≤ 5</td></tr><tr><td colspan="2">a < 1 / 2 Glass Thickness</td></tr></table>	Length and Width	Acc. Qty	c < 1.5, b < 1	N ≤ 5	a < 1 / 2 Glass Thickness																	
Length and Width	Acc. Qty																							
c < 1.5, b < 1	N ≤ 5																							
a < 1 / 2 Glass Thickness																								
03	Corner Chipping (cover lens not included): (Minor defect)	 <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td>c < 1.5, b < 0.5</td><td>Ignore</td></tr><tr><td colspan="2">a < 1 / 2 Glass Thickness</td></tr></table>	Length and Width	Acc. Qty	c < 1.5, b < 0.5	Ignore	a < 1 / 2 Glass Thickness																	
Length and Width	Acc. Qty																							
c < 1.5, b < 0.5	Ignore																							
a < 1 / 2 Glass Thickness																								
04	Crack: (Minor defect)	 A crack may enlarge, any type is not allowed.																						
05	Cover lens must be without any chips, cracks or other damage when viewed from the front.																							
06	Same / Different color spot	 <table><tr><th colspan="2">D: Diameter W: width L: length</th></tr><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td>D < 0.20</td><td>Ignore</td></tr></table> Active Area: <table><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td>0.20 < D ≤ 0.30</td><td>2</td></tr><tr><td>0.30 < D ≤ 0.50</td><td>1</td></tr><tr><td>D > 0.5</td><td>NG</td></tr></table> Viewing Area: <table><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td>D < 0.20</td><td>Ignore</td></tr><tr><td>0.20 < D ≤ 0.5</td><td>3</td></tr><tr><td>D > 0.5</td><td>NG</td></tr></table> Distance between 2 defects should be more than 15 mm.	D: Diameter W: width L: length		Diameter	Acc. Qty	D < 0.20	Ignore	Diameter	Acc. Qty	0.20 < D ≤ 0.30	2	0.30 < D ≤ 0.50	1	D > 0.5	NG	Diameter	Acc. Qty	D < 0.20	Ignore	0.20 < D ≤ 0.5	3	D > 0.5	NG
D: Diameter W: width L: length																								
Diameter	Acc. Qty																							
D < 0.20	Ignore																							
Diameter	Acc. Qty																							
0.20 < D ≤ 0.30	2																							
0.30 < D ≤ 0.50	1																							
D > 0.5	NG																							
Diameter	Acc. Qty																							
D < 0.20	Ignore																							
0.20 < D ≤ 0.5	3																							
D > 0.5	NG																							

No.	Item	Criteria (Unit: mm)		
07	Cover lens line Scratch 	Length	Width	Acc. Qty
		/	$W \leq 0.08\text{mm}$	Ignore
		$L \leq 5$	$0.08 < W \leq 0.15$	2
		$L \leq 3$	$0.15 < W \leq 0.20$	1
		-	$W > 0.2$	NG
		$L > 5$	-	NG
		Distance between 2 defects should be more than 15 mm.		
08	Printing sawtooth 	Length	Width	Acc. Qty
		/	$W \leq 0.2\text{mm}$	2
		$L \leq 2$	$0.2 < W \leq 0.3$	1
		$L \leq 2$	$W > 0.3$	NG

11.7 Classification of Defects

11.7.1 Visual defects (Except no / wrong label) are treated as minor defect and electrical defect is major.

11.7.2 Two minor defects are equal to one major in lot sampling inspection.

11.8 Identification / marking criteria

Any unit with illegible, wrong, double or missing marking / label shall be rejected.


11.9 Packing

11.9.1 There should be no damage to the outer carton box, each packaging box should have one identical label.

11.9.2 Modules inside package box should have a compliance mark.

11.9.3 All direct package materials shall offer ESD protection.

Note1: Bright dot is defined as a dot whose defective area is larger than 50% of one sub-pixel area.



Bright dot: The bright dot size defect at black display pattern. It can be recognized by 2% transparency of filter when the distance between eyes and panel is 350mm±50mm.

Dark dot: Cyan, Magenta or Yellow dot size defect at white display pattern. It can be recognized by 5% transparency of filter when the distance between eyes and panel is 350mm±50mm.

Note2: Mura on display which appears darker / brighter against background brightness on parts of display area.

12. Reliability Specification

N o	Item	Condition	Quantity	Criteria
1	High Temperature Operating	70°C, 96Hrs	2	GB/T2423.2 -2008
2	Low Temperature Operating	-20°C, 96Hrs	2	GB/T2423.1 -2008
3	High Humidity Storage	60°C, 90%RH, 96Hrs	2	GB/T2423.3 -2016
4	High Temperature Storage	80°C, 96Hrs	2	GB/T2423.2 -2008
5	Low Temperature Storage	-30°C, 96Hrs	2	GB/T2423.1 -2008
6	Thermal Cycling Test Storage	-20°C ↔ 70°C 30 min 5 min 30 min after 5 cycle, Restore 2H at 25°C Power off	2	GB/T2423.22 -2012
7	Packing vibration	Frequency range: 10Hz ~ 50Hz Acceleration of gravity: 5G X, Y, Z 30 min for each direction.	-	GB/T5170.14 -2009
8	Electrical Static Discharge	Air: ±4KV 150pF / 330Ω Contact: ±2KV 150pF / 330Ω	2	GB/T17626.2 -2018
9	Drop Test (Packaged)	Height: 72cm (weight ≤ 10kg), 60cm (weight > 10kg), 1 corner, 3 edges, 6 surfaces.	-	GB/T2423.7 -2018

Note1. No cosmetic defects and no loss of operational function are allowed.

Note2. Total current Consumption should be below twice the initial value

13. Precautions and Warranty

13.1 Safety

13.1.1 The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.

13.1.2 Since the liquid crystal cells are made of glass, do not apply strong impact on them.

Handle with care.

13.2 Handling

13.2.1 Store and use within ratings in order to keep performance and prevent damage.

13.2.2 Do not wipe the cover glass with dry cloth, as it might cause scratches. If the surface of the cover glass needs to be cleaned, wipe it swiftly with cotton or other soft cloth soaked with IPA or petroleum benzene, do not use other chemicals.

13.3 Storage

13.3.1 Do not store the LCD module beyond the specified temperature ranges.

13.3.2 Strong light exposure causes degradation of polarizer and color filter

13.4 Operation

13.4.1 Response time will increase at lower temperatures

13.4.2 Display may change color with different temperature

13.4.3 Mechanical disturbance during operation, such as pressing on the display area, may cause temporary display non-uniformity.

13.4.4 Do not connect or disconnect the LCM to or from the system when power is on.

13.4.5 Never use the LCM under abnormal condition of high temperature and high humidity.

13.4.6 Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

13.4.7 Do not display the fixed pattern for a long time (we suggest the time not longer than one hour), because it may develop image sticking due to the TFT structure.

13.5 Static Electricity

13.5.1 CMOS LSIs are equipped in this unit, so care must be taken to avoid the electro-static charge, by grounding the human body, etc.

13.5.2 The normal static prevention measures should be observed for work clothes and benches.

13.5.3 The module should be kept in anti-static bags or other containers resistant to static for storage.

14. Legal information

CE Marking

CE marking is obligatory only for complete end products. Unisystem display modules are semifinished goods designed to be integrated into finished devices and, therefore, are not CE marked.

Warranty

Unisystem grants a warranty for the proper operation of the goods for a period of 24 months from the date of delivery. If, as a result of a warranty claim, the customer receives a defect-free item as a replacement, the warranty period shall start anew from the moment the replacement is received.

Right to Change Specifications

Unisystem reserves the right to make changes to the product specifications, dimensions, and materials without prior notice in order to improve reliability, function, or design. It is the buyer's responsibility to verify that the datasheet is current before placing an order.

Intellectual Property

This document and the technical information herein are the exclusive property of Unisystem and may be subject to pending or granted patents. Reproduction or disclosure of this document without prior written permission is strictly prohibited. No intellectual property licenses are implicitly conveyed.

Limitation of Liability

Images and graphics used in this document are for illustrative purposes only. Unisystem shall not be liable to the buyer or any third party for any indirect, incidental, special, or consequential damages (including, without limitation, lost profits or business opportunities) arising from the use of its products or services.

High-Risk Applications Disclaimer

Unisystem products are not designed, intended, or authorized for use in safety-critical or high-risk applications where failure could directly result in personal injury, death, or severe environmental damage (e.g., life support machines, aerospace navigation, nuclear facilities). Using Unisystem products in such high-risk activities is entirely at the buyer's risk, and the buyer agrees to fully indemnify and hold Unisystem harmless from any damages or claims resulting from such unauthorized use.

15. Contact Information

unisystem

UNISYSTEM SP. Z O.O.

Nowy Świat 36
80-299 Gdańsk
Poland

+48 58 761 54 20
office@unisystem.com

UE VAT No:
PL5842741076