



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



SPECIFICATION

MODEL NO. : WLOF00035000XNFAAEA00

Summary

WLOF00035000XNFAAEA00 is built in TFT 3.5" IPS display. The features describe as below:

3.5 Inch Smart Display Feature


1. DC 5V working voltage.
2. UART Interface with customized UART protocol, default baud rate at 19200 bit/Sec.
3. Built in 16M flash memory.
4. WLOF00035000XNFAAEA00 is defined as a slave device, which is controlled by master device via customized command to render display content on the display screen and return touch event position.

Product information

General information

Item	Standard Value	Unit
Operating voltage	5	Vdc
Communication Interface	UART	N/A
MCU	IT9866	N/A
Flash Memory	16	MB
SDRAM Frequency	16MB/ 360MHz	
LCD display size	3.5	inch
Dot Matrix	320 x RGB x 240(TFT)	dot
Module dimension	100.0(W)*66.1(H)*10.68(D)	mm
Active area	70.08 x 52.56	mm
Dot pitch	0.073 x 0.219	mm
Brightness	400 min, 500 typ	cd/m ²
LCD type	TFT, Normally black, Transmissive	
View Direction	Wide View	
Aspect Ratio	4:3	
Touch Panel	Without Touch Panel	
Surface	Glare	

Contour Drawing



Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-30	—	+85	°C
Storage Temperature	TST	-40	—	+85	°C

Electrical Characteristics

Item	Symbol	Min	Typ	Max	Unit
Supply Voltage	VCC	4.5	5-	5.5	V
Supply current	ICC	-	340		mA

BOM

Item	Description
LCM	WF35XTWACDNN0#
PCBA	SV10003R500LA00N0100

Interface

CON2 definition:

Pin	Symbol	Function	Remark
1	GND	Power Ground	
2	UART_TX	UART TX	
3	UART_RX	UART RX	
4	+5V	Power supply 5V	
5	D+	USB Data+	
6	D-	USB Data-	
7	GND	Power Ground	
8	/REST	Reset (active Low)	
9	GND	Power Ground	
10	PWM	Pulse width modulation	
11	GND	Power Ground	
12	+5V	Power supply : 5V	

CON3 definition:

Pin	Symbol	Function	Remark
1	GND	Power Ground	
2	SW1	Switch (active low)	
3	SW2	Switch (active low)	
4	SW3	Switch (active low)	
5	SW4	Switch (active low)	
6	GND	Power Ground	
7	NC	Reserved	
8	NC	Reserved	
9	NC	Reserved	
10	NC	Reserved	
11	INT	Interrupt output for CTP or external switch	
12	+5V	Power supply : 5V	