



IDE303

Handheld Passport OCR-B/MRZ Reader



The IDE303 is a hand-held passport MRZ reader and 1D/2D bar code reader.

It can read OCR-B MRZ (Machine Readable Zone) from the passport and ID cards*; or read 1d and 2d big size PDF417 and QR codes from ID card or driver's license.



❖ Read OCR-B/ MRZ From Passport

Equipped with Megapixel 1280*1024 high-resolution CMOS image sensor, this enables the IDE303 with great performance (quick and accurate) to read the long MRZ (machine readable zone) on the passport.

❖ Read Big Size PDF417 From ID Card

Thanks to its 1280*1024 high resolution sensor, the IDE303 is readable to those big size and high-density PDF417 code from ID card / driver' license.



* Since we have not tested all ID cards from all over the world, so we do not guarantee it can read a specific ID card or not, the actual performance will be subject to the actual test.

Performance	Image Sensor	1280 * 1024 CMOS		
	Light source	Illumination:White color LED Aimer: Red color LED;		
	Symbology	OCR-B/ MRZ	Machine readable passports (MRP) : 2 lines of 44 characters (Readable distance: 13cm-24cm) Machine readable visas (MRV): 2 lines 44 characters, 2 lines 36 characters (Read distance: 12cm-24cm) Travel documents: 3 lines of 30 characters (Readable distance: 14cm-30cm)	
		2D QR PDF417	QR Code, Data Matrix, PDF417, Micro PDF417, GS1 Composite Codes , Maxi Code, Aztec, etc.	
		1D	UPCA, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, Coda bar, Code 39, Code 32, Pharmaceutical (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, GS1 Data Bar Omnidirectional, GS1 Data Bar Limited, GS1 Data Bar Expanded, China Post(Hong Kong 2 of 5), Korea Post.	
	Resolution	≥3mil (differ from different type bar codes)		
	Typical Depth of Field	MRZ	13cm-24cm	
		Code 39	70-300mm (5mil)	
		QR Code	40-310mm (15mil)	
		QR Code	40-300mm (20mil)	
		QR Code	45-550mm (30mil)	
	Motion Tolerances	40cm/s		
	Scan Mode	Sense mode, Trigger mode,Continuous mode		
Scan Angle	Roll: 360°, Pitch: ±65°, Skew:±65°			
Field of View	Horizontal 44°, Vertical 34°			
Min. Symbol Contrast	20%			
Mechanical/ Electric	Interface	USB		
	Dimensions	160mm x 70mmx 107mm		
	Weight	140g		
	Notification	Beep, LED indicator		
	Operating Power	5VDC±5%, Work Current: 266mA,Starting Current: 210mA,Stand-by Current: 130mA		
Environmental	Operating Temperature	-20°C to 60°C (-28.9°F to 140°F)		
	Storage Temperature	-30°C to 70°C (-34°F to 158°F)		
	Humidity	5% to 95% (non-condensing)		
	Shock Specifications	Designed to withstand 1.2m(5') drops		
	Ambient Light Immunity	0-100,000 Lux.		
	ESD(Electra-Static discharge)	±8kV Indirect coupling surface, ±15kV Direct air discharge		
Accessories	Cable	USB virtual Com, USB-HID		
	Stand (optional)	Hold the scanner for automatic reading.		



Tel: +86 755-23762089

Website: www.rtscan.com Email: info@rtscan.net

Room555, Floor 5, Dongming Building, Minkang Rd, 518031, Minzhi Street, Longhua District, Shenzhen, China

Copyright RTscan Technology Limited all rights reserved. IDEPASS and RTscan are registered trademark of RTscan Technology Limited. All other trademarks are the property of their respective owners. In a continuing effort to improve our products, RTscan Technology Limited reserves the right to change specifications and features without prior notice.